



# MC25

## Vari-Focal Dome Camera



### ● FEATURES

- (1) 1/3" color CCD sensor with SONY Effio DSP
- (2) High resolution
- (3) F1.4 Large aperture
- (4) f3.8 ~ f9.5mm vari-focal lens
- (5) Low light sensitivity of 0.05 Lux at F1.4
- (6) External alarm device connection
- (7) Customized OSD for camera configuration
- (8) Vandal-proof housing design (IPxx7)

### ● SPECIFICATIONS

MODEL	<b>MC25</b>
<b>Pick up Element</b>	1/3" Color CCD image sensor with SONY Effio DSP
<b>Number of Pixel</b>	768(H)x494(V) <NTSC> / 752(H)x582(V) <PAL>
<b>Resolution</b>	Super High Resolution
<b>Min. Illumination</b>	0.05 Lux / F1.4
<b>S/N Ratio</b>	More than 48dB (AGC off)
<b>Electronic Shutter</b>	1/60 (1/50) to 1/100,000 sec
<b>Lens</b>	f3.8mm ~ f9.5mm
<b>Lens Angle</b>	85.4° ~ 36°
<b>IRIS Mode</b>	AI(Default) / AES
<b>White Balance</b>	ATW
<b>Vandal-Proof Rating</b>	IPxx7
<b>Video Output</b>	1.0 Vp-p composite, 75Ω
<b>External Alarm Device Connection</b>	Alarm in
<b>Power Source (±10%)</b>	DC12V
<b>Current Consumption (±10%)</b>	75mA
<b>Dimensions (mm)**</b>	124.3(Ø) x 92(H)
<b>Net Weight (g)</b>	460
<b>Optional Peripheral</b>	AVK-T1

\* The specifications are subject to change without notice.

\*\* Dimensional Tolerance: ± 5mm